



# AUTOFEED CONVEYOR

## M9 SORTER & M108S TRIMMER COMPATIBLE

Full automation is easily achieved by adding the M9 Autofeed Conveyor with its custom low-profile Autofeed Hopper, which swaps into place in seconds, tool-free. The Autofeed Conveyor can be fed directly from the M108S Trimmer, or from the Mobius Outfeed Conveyor if your operation includes hand touch-up on the Outfeed belt.

This speed-adjustable cannabis conveyor raises your product for sorting with the Mobius M9 Sorter. The stainless-steel hopper can integrate with multiple trimmer lines for even greater automation and cost savings.

### KEY FEATURES

Stainless steel construction

Engineered specifically for cannabis processing

Washdown-rated components

Tool-free 60-second disassembly

Easily pairs with the Mobius M108S Trimmer, Mobius Outfeed Conveyor, and the M9 Sorter

Variable speed and direction controls

Hand-built in North America

GMP ready

# SPECIFICATIONS

## AUTOFEED CONVEYOR

Construction	304 Stainless Steel
Belt Material	Fully-Encased Anti-Microbial Polyurethane
Tool-Less Disassembly	Yes
Motor	1 / 10 HP
Speed Range	6 – 35 ft / min
Belt Dimensions	5" (13 cm) W 77" (196 cm) L
Overall Dimensions	26.25" (67 cm) W 66.5" (169 cm) L 65.25" (166 cm) H
Weight	180 lbs (82 kg)
Power Requirements	NA: 120 V, 1.5 A ITL: 240 V, 0.75 A
Recommended PPE	Ear Protection Eye Protection Dust Mask
Warranty	1 Year or 1,000 Hours
Motor Markings	UL, CSA, CCC, EN, CE



# INFEEED CONVEYOR

M108S TRIMMER COMPATIBLE



## FLEXIBLE CONVEYOR SOLUTIONS FOR INCREASED AUTOMATION

Automation is the key to consistent, top-quality processed cannabis and hemp. The best way to consistently feed your M108S Trimmer or seamlessly move plant material to the next stage of processing are our Mobius Conveyors. Full automation means less people are required to process your harvest, reducing processing costs, the potential for product contamination, and the uncertainty associated with seasonal or temporary workers.

Mobius has several flexible conveyor options to help you achieve full automation, including our Infeed Conveyor. Utilizing the Infeed Conveyor reduces infeed gaps that can occur with manual feeding and reduces quality control issues by enabling a visual inspection of cannabis material before it's fed into the trimmer. All Mobius conveyor solutions are customized to our equipment to ensure quick and easy set-up and cost-effective output.

## KEY FEATURES

- Stainless steel construction
- Food-grade anti-microbial polyurethane belt
- Engineered specifically for cannabis processing
- Washdown-rated components
- Tool-free 60-second disassembly
- Easily mates to the Mobius M108S Trimmer
- Adjustable height to fit your Mobius trimming workflow
- Variable speed and direction controls
- GMP ready

# SPECIFICATIONS

## INFEED CONVEYOR

Construction	304 Stainless Steel
Belt Material	Fully-Encased Anti-Microbial Polyurethane
Tool-Less Disassembly	Yes
Motor	1/10 HP
Speed Range	6 – 35 ft / min
Belt Dimensions	5" (13 cm) W 72" (183 cm) L
Overall Dimensions	18" (46 cm) W 72" (183 cm) L 45" (114 cm) H
Weight	87 lbs (39 kg)
Power Requirements	NA: 120 V, 1.5 A ITL: 240 V, 0.75 A
Recommended PPE	Ear Protection Eye Protection Dust Mask
Warranty	1 Year or 1,000 Hours
Motor Markings	UL, CSA, CCC, EN, CE





# OUTFEED CONVEYOR

M108S TRIMMER COMPATIBLE

## INCREASED QUALITY CONTROL AND PRODUCT CONSISTENCY

Create a continuous quality control system utilizing the Outfeed Conveyor attached to the M108S Trimmer. By positioning the conveyor and quality control staff on the outfeed of the trimmer, the trimmed flowers can be inspected immediately, reducing errors, lowering costs, and streamlining your harvesting process.

With a standard quality control process using the Outfeed Conveyor, you can deliver consistent, high-quality flower every harvest. The stainless steel construction and 60-second disassembly maintain the efficiency introduced by the M108S Trimmer.

## KEY FEATURES

Stainless steel construction

Engineered specifically for cannabis processing

Washdown-rated components

Tool-free 60-second disassembly

Easily pairs with the Mobius M108S Trimmer or Mobius Autofeed Conveyor

Adjustable height to fit your Mobius trimming workflow

Variable speed and direction controls

GMP ready

# SPECIFICATIONS

## OUTFEED CONVEYOR

Construction	304 Stainless Steel
Belt Material	Fully-Encased Anti-Microbial Polyurethane
Tool-Less Disassembly	Yes
Motor	1 / 10 HP
Speed Range	6 – 35 ft / min
Belt Dimensions	16" (41 cm) W 72" (183 cm) L
Overall Dimensions	27" (69 cm) W 72" (183 cm) L 31" (79 cm) H
Weight	120 lbs (54 kg)
Power Requirements	NA: 120 V, 1.5 A ITL: 240 V, 0.75 A
Recommended PPE	Ear Protection Eye Protection Dust Mask
Warranty	1 Year or 1,000 Hours
Motor Markings	UL, CSA, CCC, EN, CE

